


WJ15EDGKNHBM-3.5
PLUG-IN TERMINAL BLOCK



PCB connector
 Rated current: 9.5 A
 Rated voltage: 300 V
 Wire range: 26-16 AWG
 Pitch: 3.5 mm
 Connection method: Push-in spring connection



For reference only!version1.0

UL/CUL

Use Group	B	C	D
Rate Voltage [V]	300	50	300
Rated Current [A]	9.5	9.5	9.5
Wire Range [AWG]	26~16		
Dielectric Voltage-Withstand	1.6KV		

IEC

Overvoltage Category	III	III	II
Contamination Class	3	2	2
Rated Voltage [V]	160	160	320
Rated Current [A]	13.4	13.4	13.4
Impulse withstand voltage [KV]	2.5	2.5	2.5
Conductor cross section[solid/flexible] [mm²]	0.2-1.5		

Material

WJ15EDGKNHBM-3.5


PLUG-IN TERMINAL BLOCK

Insulation Material	PA66
Flame retardant rating	UL94V-0
Conductor Material	Copper alloy
Plating of conductor surface	Sn plated

Other Data


Pitch/Poles [mm]/[P]	3.5/2*2-2*24
Stripping Length [mm]	10-11
Screw/Torque(Max)[N.m]	/
Operating temperature [°C]	-40~+105
Soldering temperature	/
Pin dimensions [mm]	/
PCB Hole Diameter [mm]	/

Dimensions



Accessories


WJ15EDGKNHBM-3.5
PLUG-IN TERMINAL BLOCK




[WJ15EDGVHSM-3.5](#)



[WJ15EDGRHSM-3.5](#)



[WJ15EDGVHSM-THR-3.5](#)



[WJ15EDGRHSM-THR-3.5](#)